

## เคเบิลแกรน ชนิดโลหะ รุ่น PG

### Specifications

material:  
fixrue pack:  
hermetic seal:  
O-seal cirde:  
protection degree:

brass nickle-plated  
nylon plastic  
nylon plastic  
nitrile rubber  
nitrile rubber  
IP68-10 pressure  
(rotate position)  
-40°Cto 100°C, short  
time to 120°C

ambient temperature:



PG-7

PG-11

PG-29

PG-48

Type	PG	mm	Packing/bag	Price/Bath
PG 7	M12×1.5	3~6.5	100pcs./bag	@45.-
PG 9	M16×1.5	4~8	100pcs./bag	@50.-
PG 11	M18×1.5	5~10	100pcs./bag	@60.-
PG 13.5	M20×1.5	6~12	100pcs./bag	@80.-
PG 16	M22×1.5	10~14	100pcs./bag	@90.-
PG 19	M24×1.5	12~16	100pcs./bag	@100.-
PG 21	M25×1.5	13~18	100pcs./bag	@120.-
PG 25	M30×1.5	14~21	100pcs./bag	@160.-
PG 27	M30×1.5	15~23	50pcs./bag	@220.-
PG 29	M32×1.5	18~25	50pcs./bag	@260.-
PG 36	M40×1.5	22~32	10pcs./bag	@440.-
PG 42	M50×1.5	32~38	10pcs./bag	@750.-
PG 48	M63×1.5	37~44	10pcs./bag	@850.-




PG-7

PG-11

PG-29

PG-48

PG	Dimension			
	L1/ mm	L1(length)/mm	L/mm	mm
PG 7	5	10	19	14
PG 9	6	10	20	17
PG 11	6	10	21	20
PG 13.5	6.5	10	22	22
PG 16	6.5	10	23	24
PG 19	7	12	24	27
PG 21	7	12	25	30
PG 25	7	12	26	32
PG 27	7	12	28	35
PG 29	8	12	29	40
PG 36	8	15	35	50
PG 42	9	15	37	57
PG 48	10	15	38	64



IP68 dust-proof, water proof testing qualifide

\*\* บริษัทฯสงวนสิทธิ์ที่จะเปลี่ยนแปลงราคาโดยไม่ต้องแจ้งให้ทราบล่วงหน้า \*\*